## Kimua Felez Azar

## **TiOx-270**

Product description		
Product	Titanium Dioxide, Rutile pigment produced by the sulphate process.	
Properties	The grade has a high whiteness, neutral shade and good weather resistance.	
	Organic coating of the surface improves its Dispersibility in a dispersive medium.	
Surface treatment	Aluminum compounds and organic substances.	
Applications	TiOx-270 is widely used in the production of various varnishes, water-soluble paints, solvent-	
	borne paints, paints for road marking, plastics, and	
Product Information	Specification: TU 2321-001-17547702-2014, ISO 591-1: R2, ASTM D 476: Type III, CAS No.:	
	13463-67-7, EINECS No.: 236-675-5	

## **Physico-chemical properties**

min. 93	ISO 591-1
min. 97	ASTM D 3720
max. 0.28	-
max. 0.85	-
max. 0.010	ISO 787-18
3.9	ISO 787-10
max. 0.5	ISO 787-2
6.5 - 8.5	ISO 787-9
2000 - 2300	ISO 787-17
Pigment white 6	77891
24 - 25	ISO 6504-3
11 - 13	ISO 8780-4
17 - 22	ISO 787-5
96.5 - 97.0	ISO 787-1
97.0 - 98.0	ISO 787-1
1.5 - 2.0	ISO 787-1
	min. 97  max. 0.28  max. 0.85  max. 0.010  3.9  max. 0.5  6.5 - 8.5  2000 - 2300  Pigment white 6  24 - 25  11 - 13  17 - 22  96.5 - 97.0  97.0 - 98.0

- 1- Method of determination-Fritsch particle sizer analysette 22.
- <sub>2-</sub> Method of determination- Powder tablet.

## Storage and packing

- Store in dry covered warehouses.
- The warranty period of storage: 12 months from the manufacturing date.

Paper bags (25 kg), Big bag containers (500, 1000 kg).

This information is a general description of product properties and their potential fields of application. The data is based on regularly conducted analyses of their properties and also on our own and our partner's experience of their application. Since the conditions of use are beyond our control, no warranty is given or to be implies in respect of such information.